

## SONA SYNTHETICS PRODUCTS

(An ISO 9001:2015 Certified Company)

## TECHNICAL DATA SHEET SONA MIDDLE CHROME - 6010

Ver 1.0.0

## **Product Description**

| Product Name        | Middle Chrome Yellow                           |
|---------------------|--|
| CI Name             | Pigment Yellow 34                              |
| CAS Number          | 1344-37-2                                      |
| Pigment Description | Co-Precipited Lead Chromate<br>& Lead Sulphate |
| Substance Name      | Lead Sulfochromate Yellow                      |

| Product Code      | SC/M-6010                               |  |
|-------------------|---|--|
| Cl Number         | 77600 / 77603                           |  |
| EINECS Number     | 215-693-7                               |  |
| Stuctural Formula | PbCrO <sub>4.</sub> + PbSO <sub>4</sub> |  |

| Physical Properties                    |                          | Fastness Properties              | Fastness Properties |  |
|--|--------------------------|----------------------------------|---------------------|--|
| Physical Status                        | Solid Yellow Powder Form | Heat Stability (5 Min)           | 180C <sup>0</sup>   |  |
| Specific Gravity (gm/cm <sup>3</sup> ) | 5.0 - 5.5                | Water (1-5)                      | 5                   |  |
| Bulk Density(gm/cm3)                   | 0.8 - 1.0                | Acid (1-5)                       | 4                   |  |
| Oil Obserption (g/100 g)               | 25-30 (±5 gm)            | Alkali (1-5)                     | 2                   |  |
| pH Value                               | 6.5-7.0                  | Solvent Ethyl Alcohol (1-5)      | 5                   |  |
| Moisture Content                       | 1.0 % (Max)              | Solvent Mineral Turpentine (1-5) | 5                   |  |
| Residue On Sieve(45µm)                 | 0.5 % (Max)              | Solvent Xylene (1-5)             | 5                   |  |
| Conductivity                           | 500 μSm                  | Solvent Butyl Acetate (1-5)      | 5                   |  |
| Water Solubility                       | 1 % Max                  | Wether Fastness Mass Tone (1-5)  | 3                   |  |
| Opacity                                | Opaque/Semi-Opaque       | Light Fastness Mass Tone (1-8)   | 7                   |  |

| Product Tone Shade Detail |                              | Apllication Uses             |                     |
|---------------------------|------------------------------|------------------------------|---------------------|
|                           | Mass Tone                    | Air Drying Enamel Base       | Suitable            |
|                           |                              | Solvent Base                 | Suitable            |
|                           |                              | Stoving Enamel Base          | Suitable            |
|                           |                              | Powder Coating Base          | Suitable            |
|                           |                              | Emulsion Paint Base          | Suitable            |
|                           |                              | Plastic Masterbatch Base     | Limited Suitability |
|                           |                              |                              |                     |
|                           | Tint Tone                    | Coloristic properties        |                     |
|                           |                              | Coloristic properties - Tint | Strength: ±5%       |
|                           | coloristic properties - Thit | Da,Db,dE,DC,DH,DL: ±1        |                     |

The colors above have been generated electronically and should therefore not be used for comparison purposes. The colors are meant to give a first impression of the colorant shade. The information contained herein is based on our state of knowledge. Our technical advice (whether verbal, in writing solely given to or by way of trials) is the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended

**Factory:** C-1-B/2704/8, III Phase, GIDC, Vapi - 396195, Gujarat, INDIA . **Telefax:** +91-260-2410469 • **Email:** Info@sonachromes.com • **WebSite:** www.sonachromes.com