

## **SONA SYNTHETICS PRODUCTS**

(An ISO 9001:2015 Certified Company)

# TECHNICAL DATA SHEET SONA MIDDLE CHROME - 6095

Ver 1.0.0

#### **Product Description**

Product Name	Middle Chrome Yellow	
CI Name	Pigment Yellow 34	
CAS Number	1344-37-2	
Pigment Description	Co-Precipited Lead Chromate & Lead Sulphate	
Substance Name	Lead Sulfochromate Yellow	

Product Code	SC/M-6095
CI Number	77600 / 77603
EINECS Number	215-693-7
Stuctural Formula	PbCrO <sub>4.</sub> + PbSO <sub>4</sub>

#### **Physical Properties**

· ilysicai i roperties		
Physical Status	Solid Yellow Powder Form	
Specific Gravity (gm/cm <sup>3</sup> )	5.0 - 5.5	
Bulk Density (gm/cm3)	0.8 - 1.0	
Oil Obserption (g/100 g)	25-30 ( ±5 gm)	
pH Value	6.5-7.0	
Moisture Content	1.0 % (Max)	
Residue On Sieve (45um)	0.5 % (Max)	
Conductivity	500 μSm	
Water Solubility	1 % Max	
Opacity	Opaque/Semi-Opaque	

Fastness Properties		
Heat Stability (5 Min)	220-240 C <sup>0</sup>	
Water (1-5)	5	
Acid (1-5)	4	
Alkali (1-5)	3	
Solvent Ethyl Alcohol (1-5)	5	
Solvent Mineral Turpentine (1-5)	5	
Solvent Xylene (1-5)	5	
Solvent Butyl Acetate (1-5)	5	
Wether Fastness Mass Tone (1-5)	3	
Light Fastness Mass Tone (1-8)	7	

#### **Product Tone Shade Detail**

Mass Tone
Tint Tone

### **Apllication Uses**

Alkyd /Stoving Paint Base	Suitable
Powder Coation Base	Suitable
Coil Coating Base	Suitable
PVC Base Masterbatch	Suitable
PP/HDPE/LDPE Base Masterbatch	Suitable
Other Plastic Application Base	Suitable

#### **Coloristic properties**

Coloristic properties - Tint

Strength: ±5%

Da, Db, dE, DC, DH, DL: ±1

The colors above have been generated electronically and should therefore not be used for comparison purposes. The colors are meant to give a first impression of the colorant shade. The information contained herein is based on our state of knowledge. Our technical advice (whether verbal, in writing solely given to or by way of trials) is the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended

Factory: C-1-B/2704/8, III Phase, GIDC, Vapi - 396195, Gujarat, INDIA

Telefax: +91-260-2410469 Email: Info@sonachromes.com WebSite: www.sonachromes.com